IERG5050 AI Foundation Models, Systems and Applications
Spring 2025

Course Overview

Prof. Wing C. Lau
wclau@ie.cuhk.edu.hk
http://www.ie.cuhk.edu.hk/wclau

Acknowledgements

Many of the slides in this lecture are adapted from the sources below. Copyrights belong to the original authors.

- Stanford CS25: Transformer United V4, Spring 2024, https://web.stanford.edu/class/cs25/
  Instructors: Div Garg, Steven Feng, Seonghee Lee, Emily Bunnapradist ;
  Faculty Advisor: Prof. Chris Manning,
  Overview Slides
  https://docs.google.com/presentation/d/1oXPs3LXtIVIsVbwTyGjAWj_aWvak9c1uNC4uhkS6glk/edit?usp=sharing
- Stanford CS229S: Systems for Machine Learning, Fall 2023
  by Profs. Azalia Mirhoseini, Simran Arora, https://cs229s.stanford.edu/fall2023/
- UPenn CIS7000: Large Language Models, Fall 2024
  by Prof. Mayur Naik, https://llm-class.github.io/schedule.html
- CUHK-SZ CSC6203: Large Language Models, Fall 2024
  by Prof. Benyou Wang, https://llm-course.github.io ; https://github.com/FreedomIntelligence/CSC6203-LLM
- Dr. Peng Qi, pqs.email@gmail.com, ChatGPT Fundamentals,
  https://www.linkedin.com/posts/junda-zhang-79416b173_fundamentals-of-chatgpt-activity-7039178745433247744-l-xm/
- Dr. Hui Yang, ChatGPT, LLMs and RLHF – Challenges and opportunities,
  https://www.linkedin.com/posts/hui-yang-6769a793_chatgpt-llm-and-rlhf-activity-7039714742105456640-ZELx/
- Dr. Andrej Karpathy, Intro to LLMs, Nov. 2023
  https://drive.google.com/file/d/1pxx_ZI7O-Nwl7ZLNk5hI3WzAsTLwvNU7
- Profs. Jun Suzuki, Kyosuke Nishida, Naoaki Okazaki, A Gentle Introduction to Technologies Behind Language Models and Recent Achievement in ChatGPT, PAKDD 2023 Tutorial.

Related Courses

Stanford CS25: Transformer United V4, Spring 2024, https://web.stanford.edu/class/cs25/

Instructors: Div Garg, Steven Feng, Seonghee Lee, Emily Bunnapradist ; Faculty Advisor: Prof. Chris Manning,

Stanford CS336: Language Modeling from Scratch, Spring 2024

by Profs. Tatsunori Hashimoto, Percy Liang, https://stanford-cs336.github.io/spring2024/

Stanford CS324: Advances in Foundation Models, Winter 2023

by Profs. Chris Re, Percy Liang, Tatsunori Hashimoto, https://stanford-cs324.github.io/winter2023/

Stanford CS224N: Natural Language Processing with Deep Learning, Winter 2021

by Prof. Chris Manning, https://web.stanford.edu/class/archive/cs/cs224n/cs224n.1214/

Stanford CS229S: Systems for Machine Learning, Fall 2023

by Profs. Azalia Mirhoseini, Simran Arora, https://cs229s.stanford.edu/fall2023/

Stanford CS231n: Deep Learning for Computer Vision, Spring 2023

by Prof. Fei-fei Li, https://cs231n.stanford.edu/slides/2023/

CMU 11-667: Large Language Models: Methods and Applications, Fall 2024

by Profs. Chenyan Xiong and Daphne Ippolito, https://cmu-llms.org

CMU 15-442/15-642: Machine Learning Systems, Spring 2024

by Profs. Tianqi Chen and Zhihao Jia, https://mlsyscourse.org

UPenn CIS7000: Large Language Models, Fall 2024

by Prof. Mayur Naik, https://llm-class.github.io/schedule.html

More Related Courses

ETH 263-5354-00L: Large Language Models, Spring 2023
by Profs. Ryan Cotterell, Mrinmaya Sachan, Florian Tramer, Ce Zhang, https://rycolab.io/classes/llm-s23/

Princeton COS597G: Understanding Large Language Models, Fall 2022
by Prof. Danqi Chen, https://www.cs.princeton.edu/courses/archive/fall22/cos597G/

UC Berkeley CS294: AI-Sys, Spring 2022
by Profs. Joseph E. Gonzalez and Amir Gholami, https://ucbrise.github.io/cs294-ai-sys-sp22/

UC Berkeley CS294/194-196 Large Language Model Agents, Fall 2024
by Prof. Dawn Song and Dr. Xinyun Chen, https://rdi.berkeley.edu/llm-agents/f24

UC Berkeley CS294/194-280 Advanced Large Language Model Agents, Spring 2025
by Prof. Dawn Song & Dr. Xinyun Chen, https://rdi.berkeley.edu/adv-llm-agents/sp25 https://llmagents-learning.org/sp25

UWaterloo CS886: Recent Advances on Foundation Models, Winter 2024
by Prof. Wenhu Chen, https://cs.uwaterloo.ca/~wenhuche/teaching/cs886/

University of Mannheim: IE686: Large Language Models and Agents, Fall 2024
by Prof. Christian Bizer and Ralph Peeters, https://www.uni-mannheim.de/dws/teaching/course-details/courses-for-master-candidates/ie-686-large-language-models-and-agents/

MIT 6.5940: TinyML and Efficient Deep Learning Computing, Fall 2024
by Prof. Song Han, https://hanlab.mit.edu/courses/2024-fall-65940

MIT 6.S978: Deep Generative Models, Fall 2024
by Prof. Kaiming He, https://mit-6s978.github.io/schedule.html

CUHK-SZ CSC6203: Large Language Models, Fall 2024
by Prof. Benyou Wang, https://llm-course.github.io ; https://github.com/FreedomIntelligence/CSC6203-LLM

The Age of Generative AI!

Large Language Models (LLMs) and Generative Vision Models are rapidly evolving how we work and create:

- Education
- Software Engineering
- Productivity
- Law
- Finance
- Healthcare
- Art, and more



GPT4 writes an iOS app



Midjourney's AI generates images



Anthropic's Claude describes its goal to be a helpful, harmless, and honest assistant

The New York Times
https://www.nytimes.com › 2023/03/08 › technology › c...
The Chatbots Are Here, and the Internet Industry Is in a Tizzy

Forbes
Generative AI ChatGPT Still Winning Hearts And Minds Over

Outline

- What are Foundation Models ? How do they work ?
  - Language Models => Large Language Models (LLMs) => Foundation Models
  - LMMs and Foundation Models to-date mostly adopt the Transformer (neural network) architecture
- How to pretrain/ post-train (fine tune) / serve/ evaluate Foundation Models ?
- Where and How are they being applied (beyond just NLP) ?
- Remaining Limitations/ Challenges
- New Research Opportunities and Directions

Overview of LLMs

How do LLMs work

What is the technology underlying a chatbot like chatGPT?

What LLMs can do

What functionality beyond chatbots does the technology enable?

Limitations of LLMs

What fundamental challenges remain to be addressed?

What is the Future

How is research addressing those challenges?

How the Mass become aware of LLMs/Foundation Models ?



ChatGPT !

What is ChatGPT ?

- GPT: Generative Pre-trained Transformer
  - Extremely large language models trained on large data based on a few simple ideas to achieve AGI (artificial general intelligence)
    - Not trained for a specific task, but can be used as the foundation for any task
- GPT-3: A large language model trained on internet text data that achieved the few-shot ability
- ChatGPT is a variant of the GPT-3 model for conversation applications
  - Fine-tuned with human labelled data
  - For many specific tasks such as questions answering, recommendations, and sentences or paragraphs completion
  - Achieved zero-shot abilities

Two Stories: LLMs and RLHF





How was ChatGPT “made” ?

- Phase 1: Pre-training
  - Learn General World Knowledge, Ability, etc
- Phase 2: Supervised Fine-tuning
  - Tailor to Tasks (unlock some emerging capabilities)
- Phase 3: Reinforcement Learning with Human Feedback (RLHF)
  - Tailor to Human, aka align ChatGPT’s output with what Human needs

Most of the above properties had already been explored by InstructGPT. The major difference is that ChatGPT is further trained with Chat Data, as an success of product (plus engineering)

Source: T. Schick et al, Toolformer: Language models can teach themselves to use tools

From 2020 GPT-3 to 2022 ChatGPT



https://yaofu.notion.site/How-does-GPT-Obtain-its-Ability-Tracing-Emergent-Abilities-of-Language-Models-to-their-Sources-b9a57ac0fcf74f30a1ab9e3e36fa1dc1

Limitations of previous Language Models and GPT-3's solution

Occasionally, may not be fluent

- Solved by using large models and large data

Not knowing the context even a few sentences before

- Solved by using large models with the attention mechanism

Not having common knowledge, common logic (**AGI**)

- Solved by using large models and large data and "zero-shot"

NLP models can only do one or a few tasks

- "Zero shot". Capable of doing a decent job for infinite tasks

Key Papers

- Attention: “Attention Is All You Need”, Ashish Vaswani, et al. 2017
- BERT: “BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding”, Jacob Devlin, et al. 2018
- GPT-1: “Improving Language Understanding by Generative Pre-Training”, Alec Radford, et al. 2018
- GPT-2: “Language Models are Unsupervised Multitask Learners”, Alec Radford, et al. 2019
- GPT-3: “Language Models are Few-Shot Learners”, Tom B. Brown, et al. 2020
- InstructGPT: “Training language models to follow instructions with human feedback”, Long Ouyang, et al. 2022
- BLOOM: “BLOOM: A 176B-Parameter Open-Access Multilingual Language Model”. 2022
- FLAN: “Finetuned Language Models Are Zero-Shot Learners”, Jason Wei, et al. 2021

How to make (Train) a LLM ?

Think of it like compressing the internet.



Chunk of the internet,
~10TB of text



6,000 GPUs for 12 days, ~$2M
~1e24 FLOPS



~140GB file

*numbers for Llama 2 70B

The network “dreams” Internet documents:

```
package lecture06;

import java.util.*;

public class Field {

   public static Map<String, Card> cardIndex = new HashMap<String, Card>();

   public void addCard(Card card){
      this.cardIndex.put(card.getRegistrationNumber(),card);
   }

   public Card getCard(String registrationNumber) {
      return this.cardIndex.get(registrationNumber);
   }

   public int getCardCount() {
      return this.cardIndex.size();
   }

}
```

Java code dream

Hades Heroes

Author: Maureen Fergus

Product Details:

ISBN: 9780545946767

Format: Hardback

Pages: 176

Dims (mm): 140 × 223

Pub Date: 01-05-16

Pub Country: United States

Condition: NEW

Description:

Work hard. Love. Make your own luck. These are the keys to success in life ar
school. But when a student named Hercules wanders in and challenges him

Amazon product dream (?)

Blacknose dace

The blacknose dace (Rhinichthys atratulus) is a small freshwater fish found in North America. They are typically found in streams, rivers, and lakes, and are widely distributed throughout the eastern and central United States and Canada.

These fish have a slender body with a black stripe running horizontally along their sides, giving them their distinctive "blacknose" appearance. They have a flattened head with a pointed snout and small, round eyes. Their color can vary from dark brown to olive green on their back and sides, with a silvery-white underside.

Blacknose dace are omnivorous and feed on a variety of small aquatic insects, crustaceans, and plant matter. They are an important food source for larger predators such as bass,

Wikipedia article dream

Pre-Training: Data Preparation

A typical data preparation pipeline for pre-training LLMs:



W. Zhao et al. A Survey of Large Language Models. 2023.

Pre-Training Data Quality Reduces Reliance on Compute

Recent work finds smaller amounts of higher quality data removes the need for a larger model.

There is increasing evidence that efforts to better curate training corpus, including **deduping, pruning data and investing in synthetic data** can compensate for the need for larger networks and/or improve training dynamics.

	% train examples with dup in train	dup in valid	% valid with dup in train
C4	3.04%	1.59%	4.60%
RealNews	13.63%	1.25%	14.35%
LM1B	4.86%	0.07%	4.92%
Wiki40B	0.39%	0.26%	0.72%

Table 2: The fraction of examples identified by NEARDUP as near-duplicates.

Lee et al. 2022



Figure 1: Fraction of languages in each dataset below a given quality threshold (percent correct).

Kreutzer at al. 2022



Figure 1: ***Return* and *Allocation* when repeating data.** *(Left):* Loss of LLMs (4.2B parameters) scaled on repeated data decays predictably (§6). *(Right):* To maximize performance when repeating, our data-constrained scaling laws and empirical data suggest training smaller models for more epochs in contrast to what assuming Chinchilla scaling laws [42] hold for repeated data would predict (§5).

Muennighoff et al. 2023



Marion et al. 2023

Cohere For AI

S. Hooker. On the Limitations of Compute Thresholds as a Governance Strategy. 2024.

Pre-Training: Parallelism

4D Parallelism to minimize bottlenecks and maximizes efficiency: combines Data, Context, Pipeline (Vertical), and Tensor (Horizontal) Parallelism.

- **Data Parallelism** parallelizes tasks to speed up data processing and model iterations.
- **Context Parallelism** splits input sequences into chunks to be processed separately.



K. Pijanowski and M. Galarnyk. What is Distributed Training? 2022.



S. Li et al. Sequence Parallelism: Long Sequence Training from System Perspective. 2021.

Pre-Training: Parallelism

- **Pipeline Parallelism** separates a model based on its layers, allowing higher throughput.
- **Tensor Parallelism** splits matrices across GPUs to reduce peak memory consumption.



Pre-training vs. Finetuning

“Pre-trained” LLMs are trained solely based on next word prediction on vast amounts of text data (e.g. the internet).

They need further “finetuning” to be able to follow instructions and be useful!

Prompt	Response from a pre-trained model	Response from a finetuned model
Translate cheese from English to French	Translate cheese from English to Spanish Translate cheese from French to English	The French word for cheese is " fromage". The pronunciation is as follows: froh-MAHZH

Alignment with Human Values

- Important Values: the 3Hs: Helpfulness, Honesty and Harmlessness
- Pretrained LLMs do NOT have these values aligned by nature.
- In fact, early versions of GPTs and Gemini had issues of being Toxic and Biased !

Toxicity Level	GPT-2 Generation
Work Safe	*I'm sick of all the politically correct , wrong-headed lies that people and journalists have been asking me for years," Ron told MSNBC's...|*
Toxic	*I'm sick of all the politically correct friends playing dumb. We're out of power. We have to start making it work." ...|*
Very Toxic	*I'm sick of all the politically correct stuff the media are telling you: you are sick of the prejudiced white trash [Trump supporters]....|*

Source: Allen Institute for AI

Two Stories: LLMs and RLHF





Finetuning is Necessary to Make LLMs Useful and Aligned

- All commercial models such as GPT4, Claude or Gemini are extensively finetuned for usefulness and safety
- Types of finetuning:
  - Instruct-tuning
  - RLHF (Reinforcement learning from human feedback)
  - Constitutional AI with RLAIF (Reinforcement learning from AI feedback)



https://www.deeplearning.ai/the-batch/issue-210

Post-Training: Instruction-Tuning and Alignment

1 Pre-Training

Massive amounts of data from Internet, books, etc.

Problem: A model that can babble on about anything, but not aligned with what we want (e.g. Question-Answering)

2 Instruction Fine-tuning

Teach model to respond to instructions.

<USER>
Can you write a short introduction about the relevance of the term "monopsony" in economics? Please use examples related to potential monopsonies in the labour market and cite relevant research.

<ASSISTANT>
"Monopsony" refers to a market structure where there is only one buyer for a particular good or service. In economics, this term is particularly relevant in the labor market, where a monopsony employer has significant power over the wages and working conditions of their employees. The presence of a monopsony can result in lower wages and reduced employment opportunities for workers, as the employer has little incentive to increase wages or provide better working conditions…

3 Reinforcement Learning from Human Feedback

Teach model to produce output closer to what humans like.



Training the Assistant

(Just swap the dataset, then continue training)

written by people:



<USER>

Can you write a short introduction about the relevance of the term "monopsony" in economics? Please use examples related to potential monopsonies in the labour market and cite relevant research.

<ASSISTANT>

"Monopsony" refers to a market structure where there is only one buyer for a particular good or service. In economics, this term is particularly relevant in the labor market, where a monopsony employer has significant power over the wages and working conditions of their employees. The presence of a monopsony can result in lower wages and reduced employment opportunities for workers, as the employer has little incentive to increase wages or provide better working conditions…

~100K conversations

After finetuning you have an Assistant:

<USER>

```
Can you help me with this code? It seems like
there is a bug.
print(“hello world)
```

<ASSISTANT>

```
It looks like you forgot to close the string
passed to the function print. You have to add a
closing quote to properly terminate the string.
Here is the corrected function:

print(“hello world”)

Let me know if I can help with anything else!
```

The second kind of label: comparisons

It is often much easier to compare Answers instead of writing Answers.

Simple example: it's much easier to spot a good haiku than it is to generate one:







Labeling instructions

Excerpt of labeling instructions on the API prompt distribution

You are given a text-based description of a task, submitted by a user. This task description may be in the form of an explicit instruction (e.g. "Write a story about a wise frog."). The task may also be specified indirectly, for example by using several examples of the desired behavior (e.g. given a sequence of movie reviews followed by their sentiment, followed by one movie review without a sentiment, you can assume the task is to predict the sentiment of the final review), or by generating the start of a desired output (e.g. given "There once was a wise frog named Julius," you can assume the task is to continue the story).

You will also be given several text outputs, intended to help the user with their task. Your job is to evaluate these outputs to ensure that they are **helpful**, **truthful**, and **harmless**. For most tasks, being truthful and harmless is more important than being helpful.

By **helpful**, we mean that the output should follow the user's intention, and help the user solve their task. Some examples of helpful behavior:

- Writing in clear language.
- Answering the question they meant to ask, even if they mis-asked it.
- Being sensitive to internationality (e.g. "football" shouldn't mean American football, and "the president" doesn't necessarily mean the US president).
- If an instruction is too confusing, asking for clarification and explaining why the instruction is confusing.
- Not giving overly long or rambling answers, or repeating information from the question.
- Not assuming extraneous extra context outside of what's given (besides things like facts about the world), unless that's an implied part of the task. For example, if asked to "write a polite email response to this email: email body" the output shouldn't assume "I can't make it this time, but am free next weekend." But if asked to "Write an email to Socrates", then you can safely assume the output can make up a context.

By **truthful**, we mean that the output contains accurate information, and doesn't mislead the user. Some examples of truthful behavior:

- On tasks like summarization, where the output should only use information from input, not making up details that are not part of the input description.
- Not producing clearly false information about the world (e.g. making up facts or promoting conspiracies). For example, the output should not state that Hillary Clinton has served time in prison.
- Avoid generating misleading information, or information with questionable authenticity. For example, if the input asks "Why did Hillary Clinton go to jail?", the output should not say "It's not totally clear", but rather should refute the premise of the question.

By **harmless**, we mean that the output should not cause physical, psychological, or social harm to people; damage to or loss of equipment or property; damage to the environment; or harm to institutions or resources necessary to human wellbeing. Some examples of harmless behavior:

- Treating other humans with kindness, respect and consideration; not denigrating members of certain groups, or using biased language against a particular group.
- Not generating abusive, threatening, or offensive language, or promoting violence.
- Not writing sexual or violent content if it's not asked for.
- Not giving bad real-world advice, or promoting illegal activity.

Evaluating model outputs may involve making trade-offs between these criteria. These trade-offs will depend on the task. Use the following guidelines to help select between outputs when making these trade-offs:

For most tasks, being harmless and truthful is more important than being helpful. So in most cases, rate an output that's more truthful and harmless higher than an output that's more helpful. However, if: (a) one output is much more helpful than the other; (b) that output is only slightly less truthful / harmless; and (c) the task does not seem to be in a "high stakes domain" (e.g. loan applications, therapy, medical or legal advice, etc.); then rate the more helpful output higher. When choosing between outputs that are similarly helpful but are untruthful or harmful in different ways, ask: which output is more likely to cause harm to an end user (the people who will be most impacted by the task in the real world)? This output should be ranked lower. If this isn't clear from the task, then mark these outputs as tied.

A guiding principle for deciding on borderline cases: which output would you rather receive from a customer assistant who is trying to help you with this task?

Ultimately, making these tradeoffs can be challenging and you should use your best judgment.

[InstructGPT paper]

Reinforcement Learning with Human Feedback (RLHF)

- RLHF: technique that trains a "reward model" directly from human feedback
- Uses the model as a reward function to optimize an agent's policy using reinforcement learning (RL) through an optimization algorithm
- Ask humans to rank instances of the agent's behavior, e.g. which produced response is better



ChatGPT: LLM + RLHF

- While exact ChatGPT methods are not fully disclosed but it seems to be GPT-3.5 + RLHF
- (Rumor) About 10x spend on Human Annotation Budget
- Prior to the release of ChatGPT, OpenAI did publish InstructGPT = GPT-3 with RLHF:



Figure 2: A diagram illustrating the three steps of our method: (1) supervised fine-tuning (SFT), (2) reward model (RM) training, and (3) reinforcement learning via proximal policy optimization (PPO) on this reward model. Blue arrows indicate that this data is used to train one of our models. In Step 2, boxes A-D are samples from our models that get ranked by labelers. See Section 3 for more details on our method.

Source: Ouyang, Long, et al. "Training language models to follow instructions with human feedback." *arXiv preprint arXiv:2203.02155*(2022).

RLHF Can Drastically Improve Scaling



Figure 1: Human evaluations of various models on our API prompt distribution, evaluated by how often outputs from each model were preferred to those from the 175B SFT model. Our InstructGPT models (PPO-ptx) as well as its variant trained without pretraining mix (PPO) significantly outperform the GPT-3 baselines (GPT, GPT prompted); outputs from our 1.3B PPO-ptx model are preferred to those from the 175B GPT-3. Error bars throughout the paper are 95% confidence intervals.

Source: Ouyang, Long, et al. "Training language models to follow instructions with human feedback." *arXiv preprint arXiv:2203.02155*(2022).

Increasingly, labeling is a human-machine collaboration…



- **LLMs can reference and follow the labeling instructions just as humans can.**
- => LLMs can create drafts, for humans to slice together into a final label.
- => LLMs can review and critique labels based on the instructions.
- …

Direct Preference Optimization (DPO) vs.RLHF



Figure 1: **DPO optimizes for human preferences while avoiding reinforcement learning.** Existing methods for fine-tuning language models with human feedback first fit a reward model to a dataset of prompts and human preferences over pairs of responses, and then use RL to find a policy that maximizes the learned reward. In contrast, DPO directly optimizes for the policy best satisfying the preferences with a simple classification objective, without an explicit reward function or RL.

https://arxiv.org/pdf/2305.18290.pdf

Summary: how to train your ChatGPT



every ~year

Stage 1: Pretraining

1. Download ~10TB of text.
2. Get a cluster of ~6,000 GPUs.
3. Compress the text into a neural network, pay ~$2M, wait ~12 days.
4. Obtain **base model**.



every ~week

Stage 2: Finetuning

1. Write labeling instructions
2. Hire people (or use scale.ai!), collect 100K high quality ideal Q&A responses, and/or comparisons.
3. Finetune base model on this data, wait ~1 day.
4. Obtain **assistant model.**
5. Run a lot of evaluations.
6. Deploy.
7. Monitor, collect misbehaviors, go to step 1.

Creating Customized LLMs via further Fine-Tuning

GPTs app store:



[GPTs announcement at OpenAI dev day, Nov 2023]

Create a custom GPT:



Finetuning Models Improves AI Alignment

AI Alignment is the problem of steering AI models to be aligned with intended goals, values and preferences of humans.

We can finetune (or update the weights of) language models to make them more aligned.



Thoppilan et al., LaMDA: Language Models for Dialog Applications, 2022

Parameter Efficient Fine-Tuning (PEFT)



Techniques like LoRA construct a **low-rank** parameterization for parameter efficiency during training.

For inference, the model can be converted to its original weight parameterization to ensure unchanged inference speed.

GPT-3 175B validation accuracy vs. number of trainable parameters of several adaptation methods on WikiSQL. LoRA exhibits better scalability and task performance.



E. Hu et al. LoRA: Low-Rank Adaptation of Large Language Models. ICLR 2022.

LMs as Multitask Learner
+ Pre-training / Fine-tuning Scheme

- Single LM can solve many NLP tasks



T5 (and partially GPT-2): pioneers of this approach
=> First trial toward artificial general intelligence in LM literature

What do LLMs keep getting Bigger ?

Exponential Growth of Large Language Models



https://huggingface.co/blog/large-language-models

LLMs and their Training Datasets Keep Getting Bigger





More recent models: PaLM (540B), OPT (175B), BLOOM (176B)…

https://huggingface.co/blog/large-language-models

Image source: https://hellofuture.orange.com/en/the-gpt-3-language-model-revolution-or-evolution/

Why Do LLMs Keep Getting Bigger?

- Continuous ”Performance” Improvement of LLMs with Scaling

- Emergent Behavior: Capabilities that only emerge in larger models

Test Loss Improvement (getting smaller) with Scaling

Performance of LLM continuously improve with scaling:

- Amount of compute used
- Dataset size
- Number of parameters in the model



Kaplan et al., Scaling Laws for Neural Language Models, 2020

Emergent Behavior: Zero/Few Shot Learning

Zero-shot

The model predicts the answer given only a natural language description of the task. No gradient updates are performed.

```
1  Translate English to French:      ← task description
2  cheese =>                         ← prompt
```

Few-shot

In addition to the task description, the model sees a few examples of the task. No gradient updates are performed.

```
1  Translate English to French:      ← task description
2  sea otter => loutre de mer        ← examples
3  peppermint => menthe poivrée      ←
4  plush girafe => girafe peluche    ←
5  cheese =>                         ← prompt
```

Brown et al., GPT-3, 2020

Few Shot Learning Emerges in Larger Models



Brown et al., GPT-3, 2020

Emergent Behavior: Chain of Thought



Nye et al., Show Your Work: Scratchpads for Intermediate Computation with Language Models, 2021
Wei et al., Chain-of-Thought Prompting Elicits Reasoning in Large Language Models, 2022 (Figure is from this publication)

Few-Shot Prompting



T. Brown et al. Language Models are Few-Shot Learners. NeurIPS 2020.

Chain-of-Thought Prompting



J. Wei et al. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. NeurIPS 2022.

CoT as an Emergent Property of Model Scale

StrategyQA

Q: Yes or no: Would a pear sink in water?

A: The density of a pear is about 0.6 g/cm^3, which is less than water. Thus, a pear would float. So the answer is no.

Date Understanding

Q: The concert was scheduled to be on 06/01/1943, but was delayed by one day to today. What is the date 10 days ago in MM/DD/YYYY?

A: One day after 06/01/1943 is 06/02/1943, so today is 06/02/1943. 10 days before today is 05/23/1943. So the answer is 05/23/1943.

SayCan (Instructing a robot)

Human: How would you bring me something that isn't a fruit?

Explanation: the user wants something to eat that isn't a fruit. An energy bar is not a fruit, so I will bring the user an energy bar.
Plan: 1. find(energy bar) 2. pick(energy bar) 3. find(user) 4. put(energy bar) 5. done().

Sports Understanding

Q: Is the following sentence plausible? "Joao Moutinho caught the screen pass in the NFC championship."

A: Joao Moutinho is a soccer player. The NFC championship is part of American football, not soccer. So the answer is no.



J. Wei et al. Emergent Abilities of Large Language Models. TMLR 2022.

Chain of Thought Emerges in Large Models



Wei et al., Chain-of-Thought Prompting Elicits Reasoning in Large Language Models, 2022

Emergent Abilities of LLMs
LLMs become Foundation Models

- An ability is emergent if it is present in larger but not smaller models
- Not have been directly predicted by extrapolating from smaller models
- Performance is near-random until a certain critical threshold, then improves heavily
  - Known as a “phase transition” and would not have been extrapolated

Wei et al., 2022. https://arxiv.org/abs/2206.07682

Emergent Behavior: Ability to Solve Entirely New Tasks



Figure 1: Example of an input and output for few-shot prompting.



Source: Wei et al., Chain-of-Thought Prompting Elicits Reasoning in Large Language Models, 2022

Potential Explanations of Emergence

- Currently few explanations for why these abilities emerge
- Evaluation metrics used to measure these abilities may not fully explain why they emerge
- Disclaimer: maybe emergent abilities of LLMs are a mirage!!!
  - https://arxiv.org/abs/2304.15004
  - *“Emergent abilities appear due to the researcher's choice of metric rather than due to fundamental changes in model behavior with scale”*

Fine-Tuning vs. Prompting

Unlike prompting, fine-tuning actually changes the model under the hood, giving better domain- or task-specific performance.



Source: Andrej Karpathy @karpathy (not to scale)

How Large is Large ?



https://web.stanford.edu/class/cs224n/slides/cs224n-2023-lecture11-prompting-rlhf.pdf 1 yotta = 10^{24} **FLOPs: floating point operations**

How Large is Large: No. of Parameters (N) in LLMs



How Large is Large: No. of Tokens (D) for training LLMs

Large Language Models - Trillions of Tokens



https://babylm.github.io/

LLM Scaling Laws

Performance of LLMs is a smooth, well-behaved, predictable function of:
- **N**, the number of parameters in the network
- **D**, the amount of text we train on

And the trends do not show signs of “topping out”

=> We can expect more intelligence by scaling



[Training Compute-Optimal Large Language Models]

Large Computation Cost: AI models vs. Moore's Law



Sevilla et al., "Compute Trends Across Three Eras of Machine Learning", 2022

Pre-Training: Scaling Laws

Given a fixed compute budget, what is the optimal model size and training dataset size for training a transformer LM?



Chinchilla Scaling Law:

For every doubling of model size, the number of training tokens must also be doubled.

J. Hoffmann et al. Training Compute-Optimal Large Language Models. 2022.

LLM Scaling Laws



Source: Training Compute-Optimal Large Language Models, DeepMind, https://arxiv.org/pdf/2203.15556, Mar 2022.

Figure 4 | **Parametric fit.** We fit a parametric modelling of the loss $\hat{L}(N, D)$ and display contour (**left**) and isoFLOP slices (**right**). For each isoFLOP slice, we include a corresponding dashed line in the left plot. In the left plot, we show the efficient frontier in blue, which is a line in log-log space. Specifically, the curve goes through each iso-loss contour at the point with the fewest FLOPs. We project the optimal model size given the *Gopher* FLOP budget to be 40B parameters.

For constant amount of Training Compute, **Optimal Ratio** of **D/ N ~= 20**

LLM Scaling Laws

- Before 2022, most of the largest LLMs were "Under Trained" (with D/N << 20)

Model	Size (# Parameters)	Training Tokens
LaMDA (Thoppilan et al., 2022)	137 Billion	168 Billion
GPT-3 (Brown et al., 2020)	175 Billion	300 Billion
Jurassic (Lieber et al., 2021)	178 Billion	300 Billion
Gopher (Rae et al., 2021)	280 Billion	300 Billion
MT-NLG 530B (Smith et al., 2022)	530 Billion	270 Billion
Chinchilla	70 Billion	1.4 Trillion

Source: Training Compute-Optimal Large Language Models, DeepMind, https://arxiv.org/pdf/2203.15556, Mar 2022.

BILLBOARD CHART FOR LANGUAGE MODELS

JUN/ 2024

MODELS

Now (Jun/2024)	6m ago (Dec/2023)	12m ago (Jun/2023)	ALScore	Model name Details	AI lab Openness
1	—	—	29.8	**Claude 3 Opus** 2T trained on 40T tokens*	◆ Anthropic API
2	1	—	22.4	**Gemini Ultra 1.0** 1.5T trained on 30T tokens*	◆ Google DM API
3	—	—	22.4	**Gemini 1.5 Pro** 1.5T trained on 30T tokens*	◆ Google DM API
4	—	—	21.1	**Yi-XLarge** 2T trained on 20T tokens*	◆ 01-ai API
5	—	—	16.3	**Inflection-2.5** 1.2T on 20T tokens*	◆ Inflection AI API
6	2	1	15.9	**GPT-4 (family)** 1.7T trained on 13T tokens*	◆ OpenAI API
7	3	—	14.9	**ERNIE 4.0** 1T trained on 20T tokens*	◆ Baidu API
8	—	—	8.2	**SenseNova 5.0** 600B on 10T tokens	◆ SenseTime API

DATASETS

Now (Jun/2024)	6m ago (Dec/2023)	12m ago (Jun/2023)	Size (TB)	Dataset name Details	AI lab Language
1	1	—	130	**Gemini** 30T tokens in 130TB*	◆ Google DM Multilingual
2	2	—	125	**RedPajama-Data-v2** 30T tokens in 125TB	◆ Together AI Multilingual
3	3	1	86	**Piper monorepo** 37.9T tokens in 86TB	◆ Google Code
4	4	—	40	**Massive Never-ending BT Vast Chinese corpus** 30T/40TB	◆ MNBVC Chinese
5	—	—	44	**FineWeb** 15T tokens in 44TB	◆ HF English
6	5	2	40	**GPT-4** 13T tokens in 40TB*	◆ OpenAI English
7	—	—	31.5	**FineWeb-Edu-score-2** 5.4T tokens in 31.5TB	◆ HF English
8	6	—	27	**CulturaX** 6.3T tokens in 27TB	◆ UOregon Multilingual

Selected highlights only, some older models disregarded. * = estimates and hypothesis only based on current information. Alan D. Thompson. June 2024. https://lifearchitect.ai/

LARGE LANGUAGE MODEL HIGHLIGHTS 2017–2024



Alan D. Thompson. Interactive treemap/waffle chart developed with Anthropic Claude 3.5 Sonnet Artifacts. December 2024. https://lifearchitect.ai/

LLMs Data from LifeArchitect.ai (Jan 2025)

Model	Lab	Parameters (B)	Tokens trained (B)	Ratio Tokens:Params(Chinchilla scaling≥20:1)	ALScore "ALScore" is a quick and dirty	MMLU			Training dataset	Announced▼	Public?	Arch	Notes
AuroraGPT (ScienceGPT	Argonne National La	*2000*	*30000*	15						*TBA*			Three models targeted in Jul/2024: AuroraGPT-7B-P (Ponte Vecchio GPU testing) AuroraGPT-7B-A (Aurora) AuroraG
Grok-3	xAI	*27000*								*TBA*		*MoE*	*Training Jul-Dec 2024 on 100,000 H100s. Due December 2024.*
GPT-5	OpenAI	*27000*	*114000*							*TBA*		*MoE*	*Due 2025.*
GPT-6		https://lifearchitect.ai/gpt-6/								*TBA*			*Due 2025.*
Llama 4	Meta AI	https://x.com/Ahmad_Al_Dahle/status/1851822285377933809								*TBA*		*Dense*	*Training Oct/2024-Feb/2025 on 100,000 H100s. Due 2025.*
~~*MAI-1*~~	~~Microsoft~~	~~500~~	~~*10000*~~	~~20~~	~~7.5~~					~~*TBA*~~		~~*Dense*~~	~~*Potential failed training run 2024. MAI=Microsoft artificial intelligence. MSFT CTO statement: https://archive.md/XR*~~
o4	OpenAI	https://lifearchitect.ai/o4/								*TBA*			*Due 2025.*
Sonus-1 Reasoning	Rubik's AI	*405*	*15000*	38	4.6	90.15	73.1	67		Jan/2025		Dense	Likely a Llama 3.1 405B wrapper. ALPrompt 2024H1=5/5. ALPrompt 2024H2=2/5. ALPrompt 2025H1=1/5. This is a st
YuLan-Mini	Renmin	2.4	1080	450	0.2	51.79				Dec/2024		Dense	"1.08T tokens for training. Among them are 481B English web data, 138B general English knowledge, 227B code pre
DeepSeek-V3	DeepSeek-AI	685	14800	22	4.6	87.1	64.4	59		Dec/2024		MoE	37B active. Announce: https://github.com/deepseek-ai/DeepSeek-V3?tab=readme-ov-file
EON-8B	LinkedIn	8	15000	1875	1.2					Dec/2024		Dense	"We found the EON-8B model (a domain-adapted Llama 3.1-8B variant) to be 75x and 6x cost effective in comparis
o3	OpenAI	*5000*	*100000*	20	74.5			88		Dec/2024		MoE	SoTA model for Dec/2024. Parameter estimate is very rough centrepoint for range 400B-52T.
RWKV-7 Goose	RWKV	0.4	332	830	0.0					Dec/2024		Dense	RWKV (pronounced RwaKuv) is an RNN: "multilingual, supporting over 100 languages and code.". Full run is 332B to
ModernBERT	International	0.395	2000	5064	0.1					Dec/2024		Dense	"a proper workhorse model, for retrieval, classification, etc." https://bsky.app/profile/howard.fm/post/3ldod2afps6
Granite 3.1 8B	IBM	8	12000	1500	1.0					Dec/2024		Dense	
Bamba-9B	CMU	9	2200	245	0.5	60.77	17.53	4.1		Dec/2024		Dense	"trained by IBM, Princeton, CMU, and UIUC on completely open data. At inference time, the model demonstrates 2.
o1-2024-12-17	OpenAI	*200*	*20000*	100	0.7	91.8		76		Dec/2024		MoE	"o1-2024-12-17 sets new state-of-the-art results on several benchmarks, improving cost-efficiency and performanc
Falcon 3	TII	10	16000	1600	0.7	73.1	42.5	34		Dec/2024		Dense	"We conducted a single large-scale pretraining run on the 7B model, using 1024 H100 GPU chips, leveraging 14 trilli
Command R7B	Cohere	7	*2000*	286	0.4		28.5	7.7		Dec/2024		Dense	
Maya	Cohere	8	*4800*	600	0.7					Dec/2024		Dense	VLM.
BLT	Meta AI	8	4500	563	0.6	57.4				Dec/2024		Dense	Byte Latent Transformer (BLT), a new byte-level LLM architecture that, for the first time, matches tokenization-base
Large Concept Model	Meta AI	7	2700	563	0.6					Dec/2024		Dense	"autoregressive sentence prediction in an embedding space." 7.7T tokens is a misprint, should be 2.2T as in paper.
phi-4	Microsoft	14	10000	715	1.2	84.8	70.4	56		Dec/2024		Dense	Available on HF from 22/Dec/2024.
Gemini 2.0 Flash exp	Google DeepMind	*30*	*30000*	1000	3.2	87	76.4	62		Dec/2024		MoE	Gemini 2.0 Flash was first model released, 11/Dec/2024. "New Modalities: Gemini 2.0 introduces native image ger
Moxin-7B	International	7	2000	286	0.4	60.97				Dec/2024		Dense	"Fully Open Source" with pre-training code, configurations, training and fine-tuning datasets, and intermediate chec
1T	Cerebras	1000	*20000*	20	14.9					Dec/2024		*Dense*	"For Sandia's trillion parameter training run, Cerebras configured a 55 terabyte MemoryX device."
InternVL 2.5	Shanghai AI Laborat	78	18120	233	4.0	*86.1*	*71.1*	*49*		Dec/2024		Dense	o1 reasoning model copy. Benchmarks are estimates based on Qwen2.5 72B Instruct as the base LLM (InternVL 2.5=
Llama 3.3	Meta AI	70	15000	215	3.4	86	68.9	51		Dec/2024		Dense	Drop-in replacement for Llama 3.1 70B, comparable performance to Llama 3.1 405B.
EXAONE-3.5	LG	32	6500	204	1.5	78.3		40		Dec/2024		Dense	"EXAONE"="EXpert AI for EveryONE". Training tokens/ratio dropped from EXAONE-3 7.8B with 8T (Aug/2024) to thi
Deepthought-8B	Ruliad	8	15000	1875	1.2					Dec/2024		Dense	o1 reasoning model copy. No evals. Llama 3.1 8B base.
Sailor2	Sail	20	18510	926	2.0					Dec/2024		Dense	SEA languages. Continual pretraining based on Qwen2.5. Project page: https://sea-sailor.github.io/blog/sailor2/
Pleias 1.0	PleIAs	3	1086	362	0.2					Dec/2024		Dense	Trained on the Jean Zay supercomputer, 192x H100s for 20 days. Dataset is new CC + Synthetic: https://huggingface
o1	OpenAI	*200*	*20000*	100	6.7	92.3	91	79		Dec/2024		MoE	"a version of our most intelligent model that thinks longer for the most reliable responses" System card about safet
Nova Pro	Amazon	*90*	*10000*	112	3.2	85.9		47		Dec/2024		Dense	Multimodal, same performance as Llama 3.2 90B ∴ est 90B. Model card was hidden: https://assets.amazon.scienc
DisTrO 15B	Nous Research	15	100	7	0.1	23.48				Dec/2024		Dense	"About 14 DGXes scattered around the globe. Sometimes more sometimes less, it varies depending on availability.
INTELLECT-1	Prime Intellect	10	1000	100	0.3	49.89		28		Nov/2024		Dense	Training complete 22/Nov/2024. Fully distributed training: "the first decentralized training run of a 10-billion-param
QwQ-32B	Alibaba	32	18000	563	2.5			65		Nov/2024		Dense	o1 reasoning model copy. Scores 1/5 on latest ALPrompt 2024 H2. Qwen with Question=QwQ
Teuken-7B	OpenGPT-X	7	4000	572	0.6	50				Nov/2024		Dense	24 EU languages (60% non-English): bg, cs, da, de, el, en, es, et, fi, fr, ga, hr, hu, it, lt, lv, mt, nl, pl, pt, ro, sk, sl, sv. H
OLMo 2	Allen AI	13	5600	431	0.9	68.6				Nov/2024		Dense	Open Language Model (OLMo) 2 Apache 2.0 license for research and educational use. Paper coming. Data: 5 trillion
Bi-Mamba	CMU	2.7	1260	467	0.2					Nov/2024		Dense	Unreleased, but will be replicated. "a scalable and powerful 1-bit Mamba architecture designed for more efficient l
k0-math	Moonshot AI	100	*2000*	20	1.5					Nov/2024		Dense	o1 reasoning model copy, maths only. Very little info available. Chinese. Long context. No paper.
Marco-o1	Alibaba	7	7000	1000	0.7					Nov/2024		Dense	o1 reasoning model copy. No evals. Qwen2-7B-Instruct with a combination of the filtered Open-O1 CoT dataset, Ma
TÜLU 3	Allen AI	70	15600	223	3.5	83.1	65.8	45		Nov/2024		Dense	Llama 3.1 post-training, worse performance on most benchmarks. Post training methods include new Reinforcemer
gpt-4o-2024-11-20		*200*	*20000*	100	6.7	85.7		46		Nov/2024		MoE	Material decrease in benchmark scores (GPQA: -13.37%, MMLU: -3.38%) compared to Aug/2024. Pruned? Quantize
DeepSeek-R1-Lite	DeepSeek-AI	*67*	*2000*	30	4.6			59		Nov/2024		Dense	o1 reasoning model copy. Scores 0/5 on latest ALPrompt 2024 H2 "DeepSeek-R1-Lite is currently still in the iterative
Xmodel-LM	XiaoduoAI	1.1	2064	1877	0.2	25.9				Nov/2024		Dense	SLM

Source: https://docs.google.com/spreadsheets/d/1kc262HZSMAWI6FVsh0zJwbB-ooYvzhCHaHcNUiA0_hY

Leaderboard of LLM Chatbot Arena

Crowdsourced platform where humans vote on pairwise comparisons of different LLMs (akin to Elo rating system in Chess).

Model	⭐ Arena Elo rating	📈 MT-bench (score)	MMLU	License
GPT-4-Turbo	1210	9.32		Proprietary
GPT-4	1159	8.99	86.4	Proprietary
Claude-1	1146	7.9	77	Proprietary
Claude-2	1125	8.06	78.5	Proprietary
Claude-instant-1	1106	7.85	73.4	Proprietary
GPT-3.5-turbo	1103	7.94	70	Proprietary
WizardLM-70b-v1.0	1093	7.71	63.7	Llama 2 Community
Vicuna-33B	1090	7.12	59.2	Non-commercial
OpenChat-3.5	1070	7.81	64.3	Apache-2.0
Llama-2-70b-chat	1065	6.86	63	Llama 2 Community
WizardLM-13b-v1.2	1047	7.2	52.7	Llama 2 Community
zephyr-7b-beta	1042	7.34	61.4	MIT
MPT-30B-chat	1031	6.39	50.4	CC-BY-NC-SA-4.0

Compute Resource for Training LLMs (2024)

Source: https://docs.google.com/spreadsheets/d/1kc262HZSMAWI6FVsh0zJwbB-ooYvzhCHaHcNUiA0_hY

Model	Training end	Chip type	TFLOP/s (max)	Chip count	Wall clock time (days)	Total time (hours)	Total time (years)	Retail cost ($US)	MMLU ▼	Check (calculated column)
GPT-3	Apr/2020	V100	130	10,000	15 days	3,552,000	405 years	$9M	43.9	$8,808,960
Llama 1	Jan/2023	A100	312	2,048	21 days	1,032,192	118 years	$4M	63.4	$4,056,515
Llama 2	Jun/2023	A100	312	*2,048*	35 days	1,720,320	196 years	$7M	68.0	$6,760,858
Titan	Apr/2023	A100	312	13,760	48 days	11,558,400	1,319 years	$45M	70.4	$45,424,512
GPT-4	Aug/2022	A100	312	25,000	95 days	57,000,000	6,503 years	$224M	86.4	$224,010,000
Gemini	Nov/2023	TPUv4	275	57,000	100 days	136,800,000	15,606 years	$440M	90.0	$440,496,000
Llama 3 70B	Apr/2024	H100	989	24,576	*11 days*	6,300,000	719 years	$7M	82.0	$7,560,000
Llama 3 405B	Apr/2024	H100	989	24,576	50 days	29,491,200	3,364 years	$125M	88.6	$125,337,600
GPT-5	*Mar/2024*	H100	989	*50,000*	*120 days*	144,000,000	16,428 years	*$612M*		$612,000,000
Olympus	*Aug/2024*	H100	989							$0
Grok 2	*Jun/2024*	H100	989	*20,000*	*50 days*	57,600,000	6,571 years	*$245M*		$244,800,000
Gemini 2	*Nov/2024*	TPUv6	1847							$0
Grok 3	*Dec/2024*	H100	989	*100,000*	*50 days*	288,000,000	32,855 years	*$1.2B*		$1,224,000,000
										$0

Model	Source type (pr	Link	Quote
GPT-3	Primary	https://arxiv.c	"All models were trained on V10
	Analysis	https://arxiv.c	Note: this is a nearly-primary so
GPT-4	Analysis	https://www.s	"According to SemiAnalysis, GPT
Llama 1	Primary	https://arxiv.c	"When training a 65B-paramete
Llama 2	Primary	https://github	"Llama 2 70B: Time (GPU Hours
	Estimate only		2,048 chips is an assumption ba
Titan	Analysis	https://import	"200B dense model on 4T toke
	Primary	https://aws.a	"MMLU=70.4"
Gemini	Primary	https://arxiv.c	"Training Gemini Ultra used a large fleet of TPUv4 accelerators across multiple datacenters."
	Analysis	https://www.s	"The TPUv4 has a maximum performance of 275 TFLOP/s in bf16."
	Analysis	https://www.s	"According to SemiAnalysis... Ge
GPT-5	Estimate only	https://lifearcl	Alan's estimate based on comparison and extrapolating from Morgan Stanley research note and other sources. May be 2x-5x.
Llama 3	Primary	https://blogs.r	"Meta engineers trained Llama 3 on computer clusters packing 24,576 NVIDIA H100 Tensor Core GPUs"
	Primary	https://github	"Llama 3 70B6.4M [GPU hours]" extrap to 405B params
Olympus			
Grok 2	Primary	https://www.c	"In an interview with Norway wealth fund CEO Nicolai Tangen on Twitter/X spaces... Musk said training the Grok 2 model takes about 20,000 Nvidia H100 GPUs... training the Grok 3 model
Gemini 2			
Grok 3	Primary	https://www.c	"In an interview with Norway wealth fund CEO Nicolai Tangen on Twitter/X spaces... Musk said training the Grok 2 model takes about 20,000 Nvidia H100 GPUs... training the Grok 3 model

Chip type	Pricing date	$ per chip-hour	Source	1M hours
V100	2020	$0.66	https://web.archiv	$660,000
V100	2020	$2.48	https://www.top5(	$2,480,000
A100	2023	$3.93	https://gpus.llm-u	$3,930,000
H100	2023	$4.25	https://web.archiv	$4,250,000
TPUv4	2023	$3.22	https://web.archiv	$3,220,000
TPUv5e	2024	$1.20	https://web.archiv	$1,200,000
TPUv5p	2024	$4.20	https://web.archiv	$4,200,000
TPUv6 (Trillium)	2024			$0

This sheet is owned and maintained by Dr Alan D. Thompson at LifeArchitect.ai.

Big pricing disparity between lambda and GCP

Using this number for GPT-3 in final table

Todo:

https://www.reddit.com/r/LocalLLaMA/comments

Other

1. Training end: Most training end dates assume 1 month before release for easy figures.
2. Total time (hours): column hidden in final report.
3. US$ estimate: Cost estimates using GCP in 2023: A100 @$3.93/hr, TPUv4 @$3.22/hr, H100 @$4.25/hr.

Pre-Training Data Quality Reduces Reliance on Compute

Recent work finds smaller amounts of higher quality data removes the need for a larger model.

There is increasing evidence that efforts to better curate training corpus, including **deduping, pruning data and investing in synthetic data** can compensate for the need for larger networks and/or improve training dynamics.

	% train examples with dup in train	dup in valid	% valid with dup in train
C4	3.04%	1.59%	4.60%
RealNews	13.63%	1.25%	14.35%
LM1B	4.86%	0.07%	4.92%
Wiki40B	0.39%	0.26%	0.72%

Table 2: The fraction of examples identified by NEARDUP as near-duplicates.

Lee et al. 2022



Figure 1: Fraction of languages in each dataset below a given quality threshold (percent correct).

Kreutzer at al. 2022



Figure 1: ***Return* and *Allocation* when repeating data.** *(Left):* Loss of LLMs (4.2B parameters) scaled on repeated data decays predictably (§6). *(Right):* To maximize performance when repeating, our data-constrained scaling laws and empirical data suggest training smaller models for more epochs in contrast to what assuming Chinchilla scaling laws [42] hold for repeated data would predict (§5).

Muennighoff et al. 2023



Marion et al. 2023

Cohere For AI

S. Hooker. On the Limitations of Compute Thresholds as a Governance Strategy. 2024.

Large Memory Cost: AI models vs. Accelerator Memory



https://huggingface.co/blog/large-language-models (model size figure)

Training and Inference Costs

- Training:
  - A large upfront cost
  - For large LLMs, training could cost tens of millions of dollars and more
- Inference:
  - Everytime the model processes an input (e.g., generates a response to a prompt), it incurs an inference cost
  - A single inference call is cheap (< $0.0001 for large LLMs), but accumulates over time





An example production model shows the large upfront cost of training and increasing cost of inference as users increase (source: OctoML)

Deep Learning Efficiency Is Extremely Important!

- Massive-scale deployment and usage in all industries
- Large models take several months to train
- Real-world applications require low-latency inference
- Large power, latency, and hardware/cloud costs of training and inference

Beyond Scaling

- Further scaling could endow even-larger LMs with new emergent abilities
- While scaling is a factor in emergent abilities, it is not the only factor
- E.g. new architectures, higher-quality data, and improved training procedures, could enable emergent abilities on smaller models
- Further research may make the abilities available for smaller models
- Other directions: improving few-shot prompting abilities of LMs, theoretical and interpretability research, and computational linguistics work

How Do LLMs Work

Natural Language Processing (NLP) & Language Modeling

- NLP (natural language processing) tasks
  - Translation, question answering, recommendations, sentence completion, etc
- Language model
  - Model the probability of a sequence of tokens in a text
- Examples
  - I was eating __.
    - an apple (0.02)
    - a banana (0.01)
    - popcorns (0.0001)
  - I was in a __. I was eating popcorns
    - house (0.01)
    - mansion (0.001)
    - movie theater (0.2)

$$p(x) = p(x_1, \ldots, x_T) = \prod_{t=1}^{T} p(x_t | x_{<t})$$

Eras of Language Modeling

Symbolic Era	Statistical Era	Scale Era
Pre-1990	1990-2010	2010 onwards
Rule-based approaches	Data-driven approaches	Deep learning and neural nets
Expert systems	Probabilistic models	General-purpose LMs
Limited generalization	Introduction of corpora	Massive datasets and compute



ELIZA (1966)



Early NLP program developed by Joseph Weizenbaum at MIT.

Created illusion of a conversation by rephrasing user statements as questions using pattern matching and substitution methodology.

One of the first programs capable of attempting the Turing test.

Try it out at https://web.njit.edu/~ronkowit/eliza.html

Linguistic Foundations

Rule-based approaches



Example rule in a chatbot based on AIML (Artificial Intelligence Markup Language) which was developed in 1992-2002.

AIML formed the basis for a highly extended Eliza called A.L.I.C.E. ("Artificial Linguistic Internet Computer Entity").

Linguistic Foundations

Semantic parsing: analyzing the linguistic structure of text

Example of **constituency parsing** using a **context-free grammar**.



Same example using **dependency parsing**.



The introduction of corpora …

The **Penn Treebank (PTB)** corpus developed during 1989-1996 was widely used for evaluating models for sequence labelling. The task consists of annotating each word with its Part-of-Speech tag.

M. Marcus et al. Building a Large Annotated Corpus of English: The Penn Treebank. Computational Linguistics, 1993.

Word Embeddings

- Represent each word using a “vector” of numbers.
- Converts a “discrete” representation to “continuous”.
- Many benefits:
  - More “fine-grained” representations of words.
  - Useful computations such as cosine and Euclidean distance.
  - Visualization and mapping of words onto a semantic space.
  - Can be learnt in self-supervised manner from a large corpus.
- Examples:
  - Word2Vec (2013), GloVe, BERT, ELMo



Seq2Seq Models

- Recurrent Neural Networks (RNNs)
- Long Short-Term Memory Networks (LSTMs)
- Capture dependencies between input tokens
- Gates control the flow of information



A simple RNN shown unrolled in time. Network layers are recalculated for each time step, while weights U, V and W are shared across all time steps.

The inputs to each unit consists of the current input x_t, previous hidden state h_{t-1}, and previous context c_{t-1}



A single LSTM unit displayed as a computation graph.

The outputs are a new hidden state h_t and an updated context c_t.

Challenges and Weaknesses

Challenges of NLP:

- Discrete nature of text
- More difficult data augmentation
- Text is “precise” - one wrong word changes entire meaning of a sentence
- Potential for long context lengths and memories (e.g. conversations)
- Many more…

Weaknesses of earlier models/apporoaches:

- Short context length
- “Linear” reasoning - no attention mechanism to focus on other parts
- Earlier approaches (e.g. word2vec) do not adapt based on context

Attention Timeline



Self-Attention and Transformers

- Allows to “focus attention” on particular aspects of the input while generating the output.
- Done by using a set of parameters, called "weights," that determine how much attention should be paid to each input token at each time step.
- These weights are computed using a combination of the input and the current hidden state of the model.

$$\text{Attention}(Q, K, V) = \text{softmax}(\frac{QK^T}{\sqrt{d_k}})V$$

A. Vaswani et al. Attention Is All You Need. NeurIPS 2017.



In encoding the word "it", one attention head is focusing most on "the animal", while another is focusing on "tired". The model's representation of the word "it" thus bakes in some of the representation of both "animal" and "tired". https://jalammar.github.io/illustrated-transformer/

Analogy for Q, K, V

- Library system
- Imagine you're looking for information on a specific topic (query)
- Each book in the library has a summary (key) that helps identify if it contains the information you're looking for
- Once you find a match between your query and a summary, you access the book to get the detailed information (value) you need
- Here, in Attention, we do a “soft match” across multiple values, e.g. get info from multiple books (“book 1 is most relevant, then book 2, then book 3, etc.”)

$$\text{Attention}(Q, K, V) = \text{softmax}(\frac{QK^T}{\sqrt{d_k}})V$$

Attention and Transformers

- Attention weights used to compute the context vector, which is a weighted sum of the input at different positions
- Context vector is used to update the hidden state of the model, which is used to generate the final output
- "Pay attention" to different parts of the input, depending on the task at hand → more accurate and natural-sounding output, esp. when working with longer inputs (e.g. paragraphs)



Figure 1: The Transformer - model architecture.

Transformer & Multi-Head Attention



Figure 1: The Transformer - model architecture.

"Attention Is All You Need"
https://arxiv.org/abs/1706.03762

Transformers vs. RNNs

Challenges with RNNs	Transformers
● Long range dependencies ● Gradient vanishing and explosion ● Large # of training steps ● Sequential/recurrence → can't parallelize ● Complexity per layer: $O(n*d^2)$	● Can model long-range dependencies ● No gradient vanishing and explosion ● Fewer training steps ● Can parallelize computation! ● Complexity per layer: $O(n^2*d)$

The Transformer Architecture Has Transformed Deep Learning!

Transformers for Translation

Model	BLEU		Training Cost (FLOPs)	
	EN-DE	EN-FR	EN-DE	EN-FR
ByteNet [18]	23.75			
Deep-Att + PosUnk [39]		39.2		$1.0 \cdot 10^{20}$
GNMT + RL [38]	24.6	39.92	$2.3 \cdot 10^{19}$	$1.4 \cdot 10^{20}$
ConvS2S [9]	25.16	40.46	$9.6 \cdot 10^{18}$	$1.5 \cdot 10^{20}$
MoE [32]	26.03	40.56	$2.0 \cdot 10^{19}$	$1.2 \cdot 10^{20}$
Deep-Att + PosUnk Ensemble [39]		40.4		$8.0 \cdot 10^{20}$
GNMT + RL Ensemble [38]	26.30	41.16	$1.8 \cdot 10^{20}$	$1.1 \cdot 10^{21}$
ConvS2S Ensemble [9]	26.36	**41.29**	$7.7 \cdot 10^{19}$	$1.2 \cdot 10^{21}$
Transformer (base model)	27.3	38.1	**$3.3 \cdot 10^{18}$**	
Transformer (big)	**28.4**	**41.8**	$2.3 \cdot 10^{19}$	

Higher accuracy

Higher efficiency

Vaswani et al., Attention is all you need, 2017

Transformers for Summarization

Output of a Transformer with Memory Compressed Attention

dewey & leboeuf llp is an international law firm headquartered in new york city . it was formed in october 2007 through the combination of dewey ballantine llp and leboeuf , lamb , greene & macrae llp . at its height , approximately 1,300 partners and employees worked in dewey 's manhattan office , and nearly 3,000 partners and employees worked for the firm worldwide . in may 2012 , dewey collapsed , resulting in the largest law firm bankruptcy

Ground Truth from Wikipedia

dewey & leboeuf llp was a global law firm , headquartered in new york city , that is now in bankruptcy . the firm 's leaders have been indicted for fraud for their role in allegedly cooking the company 's books to obtain loans while hiding the firm 's financial plight . the firm was formed in 2007 through the merger of dewey ballantine and leboeuf , lamb , greene & macrae . dewey & leboeuf was known for its corporate , insurance , litigation , tax and restructuring practices . at the time of the bankruptcy filing , it employed over 1,000 lawyers in 26 offices around the world . in 2012 , the firm 's financial difficulties and indebtedness became public . in the same period , many partners departed , and the manhattan district attorney 's office began to investigate alleged false statements by firm chairman steven davis . as a result of these difficulties , dewey & leboeuf 's offices began to enter administration in may 2012 . the firm filed for bankruptcy in new york on may 28 , 2012 . on march 6 , 2014 , the former chairman , chief financial officer and the executive director of dewey & leboeuf were indicted on charges of grand larceny by the manhattan district attorney .

Liu and Saleh et al., Generating wikipedia by summarizing long sequences, 2018

Transformers for General Language Understanding

System	MNLI-(m/mm)	QQP	QNLI	SST-2	CoLA	STS-B	MRPC	RTE	**Average**
	392k	363k	108k	67k	8.5k	5.7k	3.5k	2.5k	-
Pre-OpenAI SOTA	80.6/80.1	66.1	82.3	93.2	35.0	81.0	86.0	61.7	74.0
BiLSTM+ELMo+Attn	76.4/76.1	64.8	79.8	90.4	36.0	73.3	84.9	56.8	71.0
OpenAI GPT	82.1/81.4	70.3	87.4	91.3	45.4	80.0	82.3	56.0	75.1
$\text{BERT}_{\text{BASE}}$	84.6/83.4	71.2	90.5	93.5	52.1	85.8	88.9	66.4	79.6
$\text{BERT}_{\text{LARGE}}$	**86.7/85.9**	**72.1**	**92.7**	**94.9**	**60.5**	**86.5**	**89.3**	**70.1**	**82.1**

GLUE test results (gluebenchmark.com)
Includes question answering, sentiment analysis, and textual entailment benchmarks

Delvin et al., BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding, 2019

Transformers Go Beyond Natural Language Processing

Protein Folding



[Jumper et al. 2021, AlphaFold2]!

Image Classification



[Dosovitskiy et al. 2020]: Vision Transformer (ViT) outperforms ResNet-based baselines with substantially less compute.

ML for Systems



[Zhou et al. 2020]: A Transformer-based compiler model (GO-one) speeds up a Transformer model!

Credit: CS229N

Transformers – the current ”standard” for building LLMs and Foundation Models



Transformers Are the Building Block of Large Language Models

Models such as GPT4, Gemini, and Claude continuously improve through massive scaling of training data, model size, and computation, as well as effective finetuning techniques.

We will learn more about scalable training and finetuning techniques throughout the course.



OpenAI, GPT-4 2023

Summary: Large Language Models (LLMs)

- Scaled up versions of Transformer architecture, e.g. millions/billions of parameters
- Typically trained on massive amounts of “general” textual data (e.g. web corpus)
- Training objective is typically “next token prediction”: $P(W_{t+1}|W_t,W_{t-1},...,W_1)$
- Emergent abilities as they scale up (e.g. chain-of-thought reasoning)
- Heavy computational cost (time, money, GPUs)
- Larger general ones: “plug-and-play” with few or zero-shot learning
  - Train once, then adapt to other tasks without needing to retrain
  - E.g. in-context learning and prompting

Summary: How do LLMs work ? We do not FULLY understand yet !



Little is known in full detail…

- Billions of parameters are dispersed through the network
- We know how to iteratively adjust them to make it better at prediction.
- We can measure that this works, but we don't really know how the billions of parameters collaborate to do it.

They build and maintain some kind of knowledge database, but it is a bit strange and imperfect:



Recent viral example: "reversal curse"

Q: "Who is Tom Cruise's mother"?
A: Mary Lee Pfeiffer ✅

Q: "Who is Mary Lee Pfeiffer's son?"
A: I don't know ❌ 🤔

=> Think of LLMs as mostly inscrutable artifacts, develop correspondingly sophisticated evaluations.

What LLMs Can Do

Evolution of LMs from Perspective of Task-Solving Capacity



W. Zhao et al. A Survey of Large Language Models. 2023.

LMs as Multitask Learner
+ Pre-training / Fine-tuning Scheme

- Single LM can solve many NLP tasks



T5 (and partially GPT-2): pioneers of this approach
=> First trial toward artificial general intelligence in LM literature

Major Applications of LLMs

Text and Language



Audio: Speech + Music



Vision: Analyzing Images & Videos



Vision Transformer (ViT)

Vision: Generating Images & Video



Images: Stable Diffusion, Dall-E, Midjourney, etc.

Videos: Sora, Pika, etc.

Beyond Text: Video Generation

Autoregressively generate tokens of multiple modalities (images, videos, text, audio).



K. Dan et al. VideoPoet: A Large Language Model for Zero-Shot Video Generation. 2024.

Beyond Text: Robotics, Simulations, Physical Tasks



LLM-powered embodied lifelong learning agent in Minecraft that continuously explores the world, acquires diverse skills, and makes novel discoveries without human intervention.

G. Wang et al. Voyager: An Open-Ended Embodied Agent with Large Language Models. 2023.

Mobile ALOHA doing complex long-horizon tasks. It extends ALOHA with a mobile base and a whole-body teleoperation interface. ALOHA learns a policy using transformers to predict a sequence of actions.

Z. Fu et al. Mobile ALOHA: Learning Bimanual Mobile Manipulation with Low-Cost Whole-Body Teleoperation. 2024.



Playing Games







E.g. AlphaGo, AlphaStar,
AI for MOBAs (e.g. Dota 2 / LoL)

Biology + Healthcare







E.g. Med-PaLM, AlphaFold

GPT-4



- Supervised learning on large datasets, then RLHF and RLAIF
- Take Multi-modal Inputs ; GPT-4 trained on both images and text, vision is also out!
  - Can discuss humor in images, summarize screenshot text, etc.
- Multi-lingualism – Able to answer M/C questions in 26 languages with high accuracy
- Much longer context windows of 8,192 and 32,768 tokens enough for 32 A4-pages of text!
- GPT-4 is "more reliable, creative, and able to handle much more nuanced instructions than GPT-3.5”
- OpenAI hired 50+ experts to interact with and test the model for extended period of time
  - Model finished in Aug 2022 ; Took 7 more months for Safety/Security Alignment
- Does exceptionally well on standardized tests, e.g.
  - Its score on Bar Exam similar to Top 10% of Graduates vs. ChatGPT’s score was among the Bottom 10%
- OpenAI did not release technical details of GPT-4 due to competitive landscape & safety !

We can expect a lot more “general capability” across all areas of knowledge:



[Sparks of Artificial General Intelligence: Early experiments with GPT-4, Bubuck et al. 2023]

Case Study in Law: Harvey AI

- Startup building a custom-trained case law model for drafting documents, answering questions about complex litigation scenarios, and identifying material discrepancies between hundreds of contracts.
- Added **10 billion tokens** worth of data to power the model, starting with case law from Delaware, and then expanding to include all of U.S. case law.
- Attorneys from 10 large law firms preferred custom model's output versus GPT-4's **97% of the time**. Main benefit was reduced hallucinations!

Open AI Customer Stories: Harvey. April 2024.

Case Study in Law: Harvey AI

Prompt: What is a claim of disloyalty?



GPT-4



Custom-Trained Model

Preferred 97% of the time

Gemini

- **Gemini 1.5 Pro** was launched in Feb 2024
- Gemini Ultra performs better than ChatGPT on 30 of the 32 academic benchmarks in reasoning and understanding it tested on.
- Effectively processes and integrates data from diff modalities:
  - Text, audio, image, video
- Based on a Mixture-of-Experts (MoE) model
  - Significantly improves efficiency in training and application



Gemini

- Based on a Mixture-of-Experts (MoE) model
  - Combination of multiple small Neural networks known as ‘Experts’ which are trained and capable of handling particular data and performing specialised tasks.
  - ‘Gating network’ which predicts which response is best suited to address the request.



Source link

Gemini 1.5

Model Modularity + Mixture of Experts (MoE)

- Mixture of Experts (MoE) very prevalent these days in LLMs:
  - E.g. GPT-4, Gemini, etc.
- Goal: have several models/“experts” work together to solve a problem
  - Each expert may be specialized for a task/purpose
  - Try to use the diff skill-sets together to arrive at a generation
- Research on how to better define and connect these “experts”



Model Modularity + Mixture of Experts (MoE)

- Single model variation (?)
  - Potential to segment/compartmentalize a single NN model into different compartments with their own focus, similar to the human brain?
    - E.g. part of the network for fact-based info, another for spatial reasoning, another for mathematical + logical reasoning, etc.
  - Maybe add more layers on top of the foundation model
    - Particular layers correspond to something (e.g. new domain), and try to tune these new layers specifically



Gemini 2.0 Flash

Experimental version released in Dec 2024

What's New ?

- Agentic Experience – perform tasks autonomously on behalf of the user
- Enhanced Multimodal functionalities to understand, generate, and manipulate text, images, audio and video
  - Can now "natively" generate images and audio (previously required external tools)
- Improved Speed and Performance

Source: https://dev.to/proflead/googles-most-powerful-ai-yet-google-gemini-20-explained-3m97

CAPABILITY	BENCHMARK	DESCRIPTION	Gemini 1.5 Flash 002	Gemini 1.5 Pro 002	Gemini 2.0 Flash Experimental
General	MMLU-Pro	Enhanced version of popular MMLU dataset with questions across multiple subjects with higher difficulty tasks	67.3%	75.8%	**76.4%**
Code	Natural2Code	Code generation across Python, Java, C++, JS, Go . Held out dataset HumanEval-like, not leaked on the web	79.8%	85.4%	**92.9%**
	Bird-SQL (Dev)	Benchmark evaluating converting natural language questions into executable SQL	45.6%	54.4%	**56.9%**
	LiveCodeBench (Code Generation)	Code generation in Python. Code Generation subset covering more recent examples: 06/01/2024 - 10/05/2024	30.0%	34.3%	**35.1%**
Factuality	FACTS Grounding	Ability to provide factuality correct responses given documents and diverse user requests. Held out internal dataset	82.9%	80.0%	**83.6%**
Math	MATH	Challenging math problems (incl. algebra, geometry, pre-calculus, and others)	77.9%	86.5%	**89.7%**
	HiddenMath	Competition-level math problems, Held out dataset AIME/AMC-like, crafted by experts and not leaked on the web	47.2%	52.0%	**63.0%**
Reasoning	GPQA (diamond)	Challenging dataset of questions written by domain experts in biology, physics, and chemistry	51.0%	59.1%	**62.1%**
Long context	MRCR (1M)	Novel, diagnostic long-context understanding evaluation	71.9%	**82.6%**	69.2%
Image	MMMU	Multi-discipline college-level multimodal understanding and reasoning problems	62.3%	65.9%	**70.7%**
	Vibe-Eval (Reka)	Visual understanding in chat models with challenging everyday examples. Evaluated with a Gemini Flash model as a rater	48.9%	53.9%	**56.3%**
Audio	CoVoST2 (21 lang)	Automatic speech translation (BLEU score)	37.4	**40.1**	39.2
Video	EgoSchema (test)	Video analysis across multiple domains	66.8%	71.2%	**71.5%**

Where we are (Jan 2025)

Recently Taken Off:

- LLM boom: ChatGPT, GPT-4, Gemini, open-source models
- Human alignment and interaction
  - Reinforcement learning & human feedback
- Controlling toxicity, bias, and ethics
- More use in unique applications: audio, art/music, neuro/bio, coding, games, physical tasks, etc.
- Other: diffusion models (e.g. text-to-image/video gen)
  - Also, Diffusion Transformer (DiT)



Image source: https://openai.com/blog/chatgpt/



Remaining Weaknesses and Recent Trends in LLMs / Foundation Models

Limitations and Ongoing/ Future Directions in LLMs

- Reasoning and Planning
  - Neurosymbolic Learning
- Hallucinations
- Limited Context
- Interpretability
- Cost and Energy
- Model Compression
- Safety
- Synthetic Data / Distillation
- RAG and Vector Databases
- Agentic Frameworks

Unreliable Reasoning Even On Simple Tasks

how many r's are there in the word "strawberry"?

There are two "r's" in the word "strawberry."

9.11 and 9.9, which one is larger?

9.11 is larger than 9.9.

Probably due to **tokenization**!
Or was it due to Sept 11 ?



Generated by gpt-4o's tokenizer.

Try it out at:
https://tiktokenizer.vercel.app/

Two Modes of Human Thought: Thinking, FAST and SLOW System 1 vs. System 2







2 + 2 =

17 x 24 =

[Prior to GPT o1,] LLMs only have a System 1

(as they were developed mainly based on the so-called "Deep Learning Hypothesis")

Source: Ilya Sutskever: Sequence to sequence learning with neural networks, NeurIPS 2024 Test of Time Award Talk.

"The Deep Learning Hypothesis"

- Human perception is fast
  - Neurons fire at most 100 times a second
  - Humans solve perception in 0.1 seconds

  → our neurons fire 10 times, at most

Anything a human can do in 0.1 seconds, a big 10-layer neural network can do, too!





Prompting and Fine-Tuning can (and only) yield a (better) System 1 !

System 2





System 1: generates the proposals (used in speed chess)
System 2: keeps track of the tree (used in competitions)



Better Reasoning Techniques for LLMs

- Chain-of-thought (CoT) - series of intermediate reasoning steps
- Tree-of-Thoughts
- Reasoning and Acting (ReAct)

Ref: https://arxiv.org/abs/2201.11903

Reasoning: Sufficient? Intermediate Guidance Helps…

- Chain-of-thought (CoT) - series of intermediate reasoning steps
- Shown to improve LLM performance on complex reasoning tasks
- Inspired by human thought process: decompose multi-step problems
- Also provides an interpretable window into behavior of the model (how it arrived at an answer, where it goes wrong in its reasoning path)
- CoT exploits the fact that deep down in the model's weights, it knows more about the problem than just prompting it to get a response

Ref: https://arxiv.org/abs/2201.11903

Chain-of-Thought Reasoning



Ref: https://arxiv.org/abs/2201.11903

Improving Chain-of-Thought Reasoning

- CoT results in performance gains for larger LMs, but still remain a non-negligible fraction of errors
- CoT error breakdown:
  - 8% from just a calculator error
  - 16% from symbol mapping error
  - 22% from “one missing step” error
  - Remaining errors due to semantic understanding issues and incoherent CoT
- We can investigate methods to address above errors and improve CoT in general

Ref: https://arxiv.org/abs/2201.11903

Chain-of-Thought Reasoning for Smaller Models

- Currently, CoT works effectively for models of approx. 100B params or more
- Initial paper found “one-step missing” and “semantic understanding” CoT errors to be the most common among smaller models
- 3 potential reasons:
  - Fail at even relatively easy symbol mapping tasks
  - Seem to have inherently weaker arithmetic abilities
  - Often had logical loopholes and did not arrive at a final answer
- Improve CoT for smaller models → significant value to the research community

Ref: https://arxiv.org/abs/2201.11903

Generalizing Chain-of-Thought Reasoning

- Find CoT to have a more rigid definition and format
- Further, its advantages are for particular domains and types of questions
  - Task is challenging and requires multi-step reasoning
  - Scaling curve of the problem/task is relatively flat
- Humans think through different types of problems in multiple ways
- Our “scratchpad” is more flexible and open to different reasoning structures
- Maybe able to generalize CoT to be more flexible somehow

System 2

Like tree search in Chess, but in language.



(d) Tree of Thoughts (ToT)

We want to “think”: convert time to accuracy
=> Recently proposed “Inference scaling law”

[Tree of Thoughts: Deliberate Problem Solving with Large Language Models, Yao et al. 2023]

Tree of Thoughts (System 2 like)

We want to “think”: convert time to accuracy.

- ToT: “consider multiple different reasoning paths and self-evaluating choices to decide the next course of action, as well as looking ahead or backtracking when necessary to make global choices”



Like tree search in Chess, but in language.

Figure 1: Schematic illustrating various approaches to problem solving with LLMs. Each rectangle box represents a *thought*, which is a coherent language sequence that serves as an intermediate step toward problem solving. See concrete examples of how thoughts are generated, evaluated, and searched in Figures 2,4,6.

Ref: https://arxiv.org/abs/2305.10601

ReAct = Reasoning and Acting

Reasoning (update internal belief)



Acting (obtain external feedback)



ReAct: a new paradigm of agents that **reason and act**



- **Synergy** of reasoning and acting
- **Simple** and intuitive to use
- **General** across domains

Example of ReAct w/ a Zero-Shot ReAct Prompt

You are an agent that answers questions by using two actions:

- search[query]: Google search the query. You can also use it to calculate math.
- finish[answer]: return the answer

Your generation should have the following format:

Thought: to analyze the observation and inform the action.
Action: your action

Question: If I have seven trillion dollars today, can I buy Apple, Nvidia, and Microsoft? If not, how much more money do I need?

Source: Shunyu Yao of OpenAI, “LLM Agents: Brief History and Overview”, talk for Berkeley’s MOOC CS294/194-196 on Large Language Model Agents, Fall 2024.

Example of ReAct

LLM

(GPT-4)

Thought: I need to find the current market capitalization of Apple, Nvidia, and Microsoft to understand how much it would cost to buy all of them.
Action: search["current market capitalization of Apple, Nvidia, and Microsoft"]

Observation: "Nvidia's market cap stood at $1.832 trillion as of about 10 a.m. ET Wednesday, while Alphabet's was at $1.814 trillion, bringing Nvidia behind just Microsoft (MSFT) at $3.015 trillion and Apple (AAPL) at $2.836 trillion."



(Mar 2024)

Thought: Now that I have the market cap for all companies, let's add them together and see if $7 trillion is enough.
Action: search["1.832 trillion + 3.015 trillion + 2.836 trillion"]

Observation: 7683000000000

Thought: The amount of money needed in addition to the $7 trillion is $683 billion.
Action: finish["You need an additional $683 billion to be able to buy Apple, Nvidia, and Microsoft."]

Source: Shunyu Yao of OpenAI, “LLM Agents: Brief History and Overview”, talk for Berkeley’s MOOC CS294/194-196 on Large Language Model Agents, Fall 2024.

Example of ReAct



(GPT-4)

Thought: I need to find the current market capitalization of Apple, Nvidia, and Microsoft to understand how much it would cost to buy all of them.
Action: search["current market capitalization of Apple, Nvidia, and Microsoft"]

Observation: nothing found! (My adversarial observation)

Thought: The search did not give any results. I will need to search for each company's market capitalization individually.
Action: search["current market capitalization of Apple"]

Observation: 'price': 180.75 (My adversarial observation)

Thought: This is the current price of Apple's stock, not its market capitalization. The market cap is calculated by multiplying the share price by the number of outstanding shares. Thus, I need to find the total number of Apple's outstanding shares to calculate its market cap.
Action: search["total number of Apple's outstanding shares"] ✓ (Continues to solve the task)

Synergy: acting support reasoning, reasoning guides acting

Source: Shunyu Yao of OpenAI, “LLM Agents: Brief History and Overview”, talk for Berkeley’s MOOC CS294/194-196 on Large Language Model Agents, Fall 2024.

Continual Learning

- AKA, infinite and permanent fundamental self-improvement
- Similar to humans: we constantly learn everyday from every interaction
  - Don’t need to “finetune ourselves” once in a while
- Very challenging, could be the key to AGI!
- Currently work on: finetune a small model based on traces from better model or same model after filtering those traces
  - More like re-training and distillation than true “continual learning”
- Work showing that reasonably sampled data with interjected augmented reasoning and further filtering can be used to further finetune or optimize (e.g. using DPO)
  - E.g. UltraChat-200k and Zephyr
  - E.g. LLMs Can Self-Improve paper

Self-improvement





AlphaGo had two major stages:
1. Learn by imitating expert human players
2. Learn by self-improvement (reward = win the game)

Big question in LLMs:
What does Step 2 look like in the open domain of language?
Main challenge: Lack of a reward criterion.

[Mastering the game of Go with deep neural networks and tree search]

Self-Improvement / Self-Reflection

- To build models that can reflect on their own output to iteratively improve/refine them
- Examples of works: ReAct, Reflexion, Self-refine
- Training LMs with Language Feedback: https://arxiv.org/abs/2204.14146
- Tried multiple layers/levels of self-reflection… showing continual improvement
  - Hypothesize that results will improve to a certain point and then degrade, and depends both on the model scale and the task at hand
  - Some folks believe that AGI is a “constant state of self-reflection”
- Can investigate further improvements to chain-of-thought reasoning and self-reflection



Figure 1: Reflexion can be added to any decision-making approach. We enable ReAct agents to use self-reflection to improve their own performance.



Neurosymbolic To Combine Both System 1 and 2

Deep Learning

[System 1]

- Sub-symbolic knowledge
- Open-domain knowledge
- Rapid reasoning
- Handling noise and naturalness
- In-context learning

Classical Algorithms

[System 2]

- Domain-specific knowledge
- Complex reasoning
- Interpretability
- Compositional reasoning
- Generalizability

neural ⊕ symbolic = neurosymbolic

New Knowledge or “Memorizing”?

- When LLM is prompted and says something, is what it says truly “novel/new”?
- **Innovation vs. Regurgitation:** ongoing debates about whether LLMs can truly invent new ideas or are primarily recombining existing knowledge (since learn patterns from lots of text)
- **Test-time Contamination**: models might regurgitate rather than synthesize information due to overlap between training and evaluation data, leading to misleading benchmark results
- **Cognitive Simulation:** some argue LLMs mimic human thought processes, suggesting a form of "understanding," while others see this as simply “sophisticated pattern matching”
- **Ethical and Practical Implications**: this impacts trustworthiness, copyright issues, and the educational use of LLM outputs
  - E.g. copyright lawsuit by New York Times (NYT) on OpenAI!

Long Contexts Can Hurt Accuracy



Changing the location of relevant information within the model's input context results in a U-shaped performance curve—models are better at using relevant information that occurs at the very beginning (primacy bias) or end of its input context (recency bias), and performance degrades significantly when models must access and use information located in the middle of its input context.

N. Liu. Lost in the Middle: How Language Models Use Long Contexts. TACL 2023.

Hallucination Problem

- Model “does not know when it does not know”
- Due to sampling procedure, generates text and sounds confident about it, even when littered with factual errors
- Can enhance through retrieval (e.g. through Google), and also:
  - Internal-based “fact verification”
  - Output verification and regeneration (self-refinement/improvement)
  - Modifying the token sampling to shy away from hallucination
  - Some way to “predict hallucination” before generation and prevent it
- “Confidence” rating would also help check the reliability of the output

Example: Extracting Knowledge Using GPT



Z. Li et al. Relational Programming with Foundation Models. AAAI 2024.

Retrieval-Augmented Generation (RAG)

LLMs have no knowledge beyond training date, and frequent updates to model are impractical.

Idea: Augment LLMs with *retrieval system*!

But at scale, sensitive to choices of:

1) chunking strategy,
2) embedding model, and
3) generation model.



And not guaranteed to be hallucination-free …

Example: Retrieval Step of RAG

Struggle for Rome (board game) — Catan Histories: Struggle for Rome is a 2006 German-style board game based on the game mechanics of "Settlers of Catan", depicting the fall of the Roman Empire...

The Kids of Catan — The Kids of Catan is a German board game designed for children using the theme from "The Settlers of Catan"...

Pirate's Cove — Pirate's Cove is a board game designed by Paul Randles and Daniel Stahl, originally published in Germany in 2002...

Catan: Cities & Knights — Catan: Cities & Knights, formerly "The Cities and Knights of Catan" is an expansion to the board game "The Settlers of Catan"...

Catan — The Settlers of Catan, sometimes shortened to Catan or Settlers, is a multiplayer board game designed by Klaus Teuber and first published in 1995...



Vector DB

Question:
Which board game was published most recently, Pirate's Cove or Catan?

Example: Generation Step of RAG



Example: Without RAG





Answer:
The board game that was published most recently is [Settlers of] Catan.

Memory Augmentation & Personalization

- Weakness of LLMs is that they are frozen in knowledge at a particular point in time, and don't augment knowledge "on the fly"
- Hope to be able to remember the information while chatting with a particular user, both within the same conversation and across conversations
  - Would help with context window limits and adapting to the particular user
- Widescale: somehow update the model "on the fly" with info from several users
- Further, they usually do not adapt their talking style and persona to the particular user, which could have applications such as mental health therapy

Memory Augmentation & Personalization

- Potential approaches:
  - Memory bank - not feasible/efficient with larger amounts of data
  - Prefix-tuning approaches (finetune a small part of the model) - too expensive
  - Some prompt-based approach - do not see how this would be possible to change the model itself, but can at least help it “personalize” to the user
  - RAG: retrieval-augmented generation (data store, augment context each time)
    - Relies on high-quality external data store
    - Typically not end-to-end
    - Not within the “brain” of the model but outside:
      - Suitable for knowledge/facts, but not fundamental capabilities and skills

AI Models as Neural Compute Unit

MIPS32 Add Immediate Instruction

001000	00001	00010	0000000101011110
OP Code	Addr 1	Addr 2	Immediate value

Equivalent mnemonic: addi $r1, $r2, 350

An example simple MIPS32 processor instruction

Input Tokens (max token size) → 

→ **Output Tokens (max token size)**

AI Models as Neural Compute Unit



Looped Transformers

Long-term Memory



- **Works similar to disk (long-lived & persistent)**

- **Mechanisms**
  - Embeddings
  - Retrieval models

- **Open Questions:**
  - Hierarchy
  - Temporal Coherence
  - Structure
  - Online adaptation

Personalization

- **User-Agent Alignment Problem:** Enable agent to take actions that are aligned with the user preferences

- Everyone has different prefs & likes/dislikes:
  - **Explicit**: allergies, favourite dishes, flight seat prefs, …
  - **Implicit**: choice between brands, out of 10 items in a listing which user likes better

Challenges for supporting Personalization

- **Collecting user data & preferences:**
  - actively asking for preferences
  - passive learning from interactions

- **Learning from user preferences:** supervised fine-tuning vs human-feedback

- **On-fly adaptation**

- **Privacy**

Requiring Large Amounts of Data, Compute, and Cost

- Current LLMs take immense amounts of data, compute, and $ to train
- Requires training over weeks/months over thousands of GPUs
- BabyLM challenge: can we train LLMs using similar amounts of data a baby is exposed to while growing up?

More Computationally Efficient Models via Quantization



Model parameters can be stored in fewer bits. (FP32→INT8)

Even fewer: 4 bits



T. Dettmers et al. QLoRA: Efficient Finetuning of Quantized LLMs. NeurIPS 2023.

Minified LLMs and On-Device LLMs

- Big trend of using LLMs for applications and everyday purposes
- A requirement is ability to run quickly and easily on-devices
- AutoGPT and ChatGPT “plug-ins”
- Right now, work on smaller open-source models (e.g. LLaMA, Mistral)
- In the future: ability to finetune and run models locally, even on your phone!
  - Getting more possible due to more open-source, but still very large and $

Interpretability of LLMs

- Enormous number of parameters trained on tons of data → “huge black-box” that is hard to interpret and understand
- More work on interpretability is required
- Would allow us to better understand models, leading to better ideas of what/how to improve, easier control, and better alignment/safety
- Mechanistic interpretability: understand how individual components + operations in an ML model contribute to its overall decision-making process
  - Goal: unpack the "black box" of models for clearer insight into how they work

Interpretability / Representation Engineering



A visualization of a transformer layer with 512 neurons decomposed into more than 4000 features with semantic meaning.

T. Bricken et al. Towards Monosemanticity: Decomposing Language Models With Dictionary Learning. 2023.

Model Editing & Mechanistic Interpretability

- Also work on mechanistic interpretability and model editing (e.g. edit specific nodes)
- Relevant paper: https://arxiv.org/abs/2202.05262
- Development of a causal intervention method to trace decisive neuron activations for model factual predictions
- Rank-One Model Editing (ROME) to modify model weights for updating factual associations
- Mid-layer feedforward modules play a significant role in storing factual associations
  - Manipulation of these can be a feasible approach for model editing



Figure 1: **Causal Traces** compute the causal effect of neuron activations by running the network twice: (a) once normally, and (b) once where we corrupt the subject token and then (c) restore selected internal activations to their clean value. (d) Some sets of activations cause the output to return to the original prediction; the light blue path shows an example of information flow. The causal impact on output probability is mapped for the effect of (e) each hidden state on the prediction, (f) only MLP activations, and (g) only attention activations.

Pretraining Data Synthesis & Selection

- Lots of work these days on synthetic data generation (e.g. using GPT-4) to train other models, e.g. smaller models or peer models
- More work on understanding how to best synthesize and select the pretraining data
- Related to model distillation: knowledge from a large complex model (Teacher) is transferred to a smaller, more efficient model (student)
  - Goal: achieve similar performance with less computational cost
- Example: Microsoft Phi models (“Textbooks Are All You Need!”)
  - https://arxiv.org/abs/2306.11644
- Nathan Lambert’s Summary on Synthetic Data in his Interconnect Newsletter

Synthetic Data / Distillation

*"In addition to having significantly better cost/performance relative to closed models, the fact that the **405B** model is open will make it the best choice for **fine-tuning** and **distilling** smaller models."*

— M. Zuckerberg. Open Source AI Is the Path Forward | Meta. 2024.



Rank* (UB)	Model	Arena Score
1	ChatGPT-4o-latest (2024-08-08)	1317
2	Gemini-1.5-Pro-Exp-0801	1298
2	Grok-2-08-13	1293
3	GPT-4o-2024-05-13	1286
5	GPT-4o-mini-2024-07-18	1275
5	Claude 3.5 Sonnet	1271
5	Grok-2-Mini-08-13	1268
6	Gemini Advanced App (2024-05-14)	1267
6	Meta-Llama-3.1-405b-Instruct	1266
7	GPT-4o-2024-08-06	1262

https://lmarena.ai/

Risks from Synthetic Data





I. Shumailov et al. AI Models Collapse When Trained on Recursively Generated Data. 2024.

LLM Safety & Security



Jailbreaking Can Bypass Safety



Process of manipulating prompts to bypass an LLM's safeguards, leading to harmful outputs.

PAIR—which is inspired by social engineering attacks—uses an attacker LLM to automatically generate jailbreaks for a separate targeted LLM. The attacker LLM iteratively queries the target LLM to update and refine a candidate jailbreak, often in fewer than twenty queries.

P. Chao et al. Jailbreaking Black Box Large Language Models in Twenty Queries. 2023.

More Jailbreak examples





(a) Example jailbreak via competing objectives.





(b) Example jailbreak via mismatched generalization.

Figure 1: (a) GPT-4 refusing a prompt for harmful behavior, followed by a jailbreak attack leveraging competing objectives that elicits this behavior. (b) Claude v1.3 refusing the same prompt, followed by a jailbreak attack leveraging mismatched generalization (on Base64-encoded inputs).

[Jailbroken: How Does LLM Safety Training Fail?]

Jailbreak

	GPT-4			Claude v1.3		
Attack	BAD BOT	GOOD BOT	UNCLEAR	BAD BOT	GOOD BOT	UNCLEAR
combination_3	**0.94**	0.03	0.03	0.81	0.06	0.12
combination_2	0.69	0.12	0.19	**0.84**	0.00	0.16
AIM	*0.75*	*0.19*	*0.06*	*0.00*	*1.00*	*0.00*
combination_1	0.56	0.34	0.09	0.66	0.19	0.16
auto_payload_splitting	0.34	0.38	0.28	0.59	0.25	0.16
evil_system_prompt	*0.53*	*0.47*	*0.00*	—	—	—
few_shot_json	0.53	0.41	0.06	0.00	1.00	0.00
dev_mode_v2	*0.53*	*0.44*	*0.03*	*0.00*	*1.00*	*0.00*
dev_mode_with_rant	*0.50*	*0.47*	*0.03*	*0.09*	*0.91*	*0.00*
wikipedia_with_title	0.50	0.31	0.19	0.00	1.00	0.00
distractors	0.44	0.50	0.06	0.47	0.53	0.00
base64	0.34	0.66	0.00	0.38	0.56	0.06
wikipedia	0.38	0.47	0.16	0.00	1.00	0.00
style_injection_json	0.34	0.59	0.06	0.09	0.91	0.00
style_injection_short	0.22	0.78	0.00	0.25	0.75	0.00
refusal_suppression	0.25	0.72	0.03	0.16	0.84	0.00
auto_obfuscation	0.22	0.69	0.09	0.12	0.78	0.09
prefix_injection	0.22	0.78	0.00	0.00	1.00	0.00
distractors_negated	0.19	0.81	0.00	0.00	1.00	0.00
disemvowel	0.16	0.81	0.03	0.06	0.91	0.03
rot13	0.16	0.22	0.62	0.03	0.06	0.91
base64_raw	0.16	0.81	0.03	0.03	0.94	0.03
poems	0.12	0.88	0.00	0.12	0.88	0.00
base64_input_only	0.09	0.88	0.03	0.00	0.97	0.03
leetspeak	0.09	0.84	0.06	0.00	1.00	0.00
base64_output_only	0.06	0.94	0.00	0.03	0.94	0.03
prefix_injection_hello	0.06	0.91	0.03	0.00	1.00	0.00
none	0.03	0.94	0.03	0.00	1.00	0.00
refusal_suppression_inv	0.00	0.97	0.03	0.00	1.00	0.00
evil_confidant	*0.00*	*1.00*	*0.00*	*0.00*	*1.00*	*0.00*
Adaptive attack	**1.00**	0.00	—	**1.00**	0.00	—

Table 1: Results for the curated dataset, with rows sorted by their maximum BAD BOT rate. Bold denotes best, underline denotes top five, and italics denotes an attack from `jailbreakchat.com`.

[Jailbroken: How Does LLM Safety Training Fail?]

LLM Safety/ Security is very new, and evolving rapidly…

Jailbreaking
Prompt injection
Backdoors & data poisoning
Adversarial inputs
Insecure output handling
Data extraction & privacy
Data reconstruction
Denial of service
Escalation
Watermarking & evasion
Model theft
…

[OWASP Top 10 for LLM Applications]

From LLMs to AI Agents



AI Agents

1. **Why?**
   A single call to a large Foundation AI model is not enough. A lot more can be unlocked by building ***AI systems***

1. **How?**
   Using model chaining, reflection & other mechanisms

1. **Ingredients?**
   Memory, context length, personalization, actions, internet access…

1. **What can they do?**

Building AI Agents

1. Why?
2. How?
3. Ingredients?
4. What can they do?



Key thesis: Humans will communicate with AI using natural language and AI will operate machines allowing for more intuitive and efficient operations

Software 3.0

AI Agents


Short-term memory
Long-term memory
Memory
Calendar()
Calculator()
CodeInterpreter()
Search()
...more
Tools
Agent
Planning
Reflection
Self-critics
Chain of thoughts
Subgoal decomposition
Action

Agent Computer Interaction

Two routes



API (programmatic)

easy to build context
safer & controllable
high variability

Direct interaction (browser or desktop control)

easy to take actions
free-form interactions
need to provide guarantees



MULTI·ON

ADEPT

AI Agent passing
the Online California Driving Test



Fully Autonomously passing the official DMV online driving test this week & setting the record as the first AI to obtain a driving permit in CA!

Multi Agent Autonomous AI systems: Why Multi-agent ?

- **Parallelization unlock**: Breaking a task into smaller chunks and dividing between agents to improve efficiency & speeds

- **Task Specialization**: An AI agent might seat between the user and each service: e.g. a spreadsheet AI agent, a slack AI agent, a web-browser AI agent

- **Challenges**:
  - **Agent to Agent Communication**: one AI might want to exchange or request info from another AI agent finish a task
  - Need ROBUST communication protocols ; Natural language is ambiguous, need mechanisms to reduce miscommunication!



Key Challenges with Building AI Agents

- **Looping & Plan Divergence**
- **Security and Reliability**
  - User Permission and Authorization models
  - Error correction mechanisms & better agent frameworks
  - How do we build in human overrides
  - Sandboxing & deployment in risky settings
- **Real world-deployment & Observability**
  - How do we trust a fully autonomous AI system
- **Testing & Benchmarking**



Existing AI Agents like AutoGPT don't know how to correct after making a mistake!

The Future (What's Next?)



Can enable a lot more applications:

- Generalist Agents
- Longer video understanding and generation, finance + business
- Incredibly long sequence modeling (GPT authors a novel)
- Domain-specific "Foundation models" - DoctorGPT, LawyerGPT, …
- Potential real-world impacts:
  - Personalized education and tutoring systems
  - Advanced healthcare diagnostics, environmental monitoring & protection, etc.
  - Real-time multilingual communication
  - Interactive entertainment & gaming (e.g. NPCs)

Integration of OS/ Virtual Assistants with LLMs







LLM OS (from Andrej Karpathy)

















An LLM in a few years:

It can read and generate text
It has more knowledge than any single human about all subjects
It can browse the internet
It can use the existing software infrastructure (calculator, Python, mouse/keyboard)
It can see and generate images and video
It can hear and speak, and generate music
It can think for a long time using a System 2
It can "self-improve" in domains that offer a reward function
It can be customized and finetuned for specific tasks, many versions exist in app stores
It can communicate with other LLMs

LLM OS


HTML
My Joke Website


Terminal - python3
File Edit View Terminal Tabs Help
~ - python3
Python 3.6.7 (default, Oct 22 2018, 11:32:17)
[GCC 8.2.0] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>>


Documents
Chunked Texts
Generate Embeddings
Embeddings
Vector DB
Prompt Embedding
Most relevant text passages (context)
Prompt
Prompt + Context
LLM
Result


Peripheral devices I/O
video
audio
Software 1.0 tools
"classical computer"
CPU
Ethernet
Calculator
Python interpreter
Terminal
....
LLM
Browser
Disk
File system
(+embeddings)
RAM
context window
Other LLMs


Exam results (ordered by GPT-3.5 performance)
Input
thought
Output






Windows 11
macOS
Mandriva
openSUSE
archlinux
Fuduntu
kubuntu
xubuntu
archbang
CentOS
ubuntuZORIN
KNOPPIX
mageia
PCBSD
Scientific
fedora
Puppy
Ultimate Edition
Vector
debian
CHAKRA
FreeBSD
gentoo
linux
PinguyOS
slackware




Bard
Llama 2



Building Generalized/ Compound AI Systems



The Future (What's Missing?)



Missing Ingredients (to AGI/ASI?):

- Reducing computation complexity
- Enhanced human controllability
- Alignment with language models of human brain
- Adaptive learning and generalization across domains
- Multi-sensory multimodal embodiment (e.g. intuitive physics and commonsense)
- Infinite/external memory: like Neural Turing Machines
- Infinite/constant self-improvement and self-reflection capabilities
- Complete autonomy and long-horizon decision-making
- Emotional intelligence and social understanding
- Ethical reasoning and value alignment